



APPLICATIONS

- A/V corporate, retail and education applications
- BGM & Paging solutions, with message priorities and source/volume independent selection
- Integration in installation global control systems
- P.A. management
- Installations requiring remote supervision, diagnostic and adjustment via Internet

MIM01212SG (MIM01212 SINGLE) is an EclerNet digital audio device that keeps the heart and soul of the standard MIM088, its main features and its audio quality, to become a simplified and cost-effective version (12x12) of this acclaimed digital matrix.



MIM01212SG

MIM01212SG

KEY FEATURES

- 12x12 digital matrix (not expandable)
- Fully programmable and controllable via EclerNet software
- UCP (User Control Panels) remote control system, compatible with WPmSCREEN and third-party devices, such as computers, tablets, smartphones, etc.
- TP-NET protocol compatible, for third-party control systems integration
- DSP processing: signal generator, delays, full parametric EQ filters at inputs and outputs, inputs noise gate, level, mute, phase, vu-meters, outputs compressor / limiter, paging and ducking (priority & overriding), virtual and physical paging stations management, presets save & recovery, scheduled events triggering, etc.
- FREQUENCY SHIFTER function to avoid acoustic feedback, available in 4 inputs



	MIM01212SG
Inputs	12 MIC/LINE Bal. (Euroblock)
Outputs	12 Bal. (Euroblock)
Communication Interfaces	1 Ethernet + 1 RS232
Remote control	8 GPI + 1 Digital control bus
Dimensions / Weight	1RU x 266,5mm depth / 3,5 kg.

ACCESSORIES

- MPAGE16
- WPTOUCH
- WPm Series
- WPmSCREEN

